

Datasheet – Gateway Ramal 16/24/32 Portas FXS



Características GATEWAYS FXS 16,24,32 PORTAS

Interfaces Físicas

RJ 11: 24/32FXS

Interface de Rede 4 portas: RJ-45 10/100Mbps,RJ45

Voz e Fax

G.711A/U law, G.723.1, G.729A/B,G.726,iLBC,AMR

Redução de Ruidos(CNG)

Voice Activity Detection(VAD)

Echo Cancellation via hardware(G.168)

Adaptive (Dynamic) Jitter Buffer

Hook Flash

Configuração de Ganho (Gain Control)

T.38/Pass-through, up to 14.4kbps

Modem/POS

DTMF Mode

Signal/RFC2833/INBAND

Serviços Adicionais

Chamada em Espera

Blind Transfer

Attend Transfer

Call Pickup

Call Forward on Busy

Call Forward on No Reply

Unconditional Call Forward

Hotline

Call Hold

DND

3-way conference

Voicemail

Features de Rede

Static IP, PPPoE, DHCP Client

IPv4, IPv6

Static/dynamic ARP

Traffic Shaping

Voice/Data/Management VLAN

DIFFServ, ToS

Porta FXS

Conector: RJ45

Dial Mode: DTMF and Pulse

Pulse: 10 and 20 PPS

Caller ID: DTMF/FSK

Tamanho Maximo do cabo: 5KM

Inversão de Polaridade

Protocolo

SIP V2.0 (RFC 3261,3262,3264)

IMS/3GPP

SDP (RFC 2327)

REFER (RFC 3515)

RTP/RTCP (RFC 1889,1890)

STUN (RFC 3489)

ARP/RARP (RFC 826/903)

SNTP (RFC 2030)

DHCP/PPPoE

TFTP/HTTP/HTTPS

DNS/DNS SRV (RFC 1706/RFC 2782)

VLAN 802.1P/802.1Q

Chamada e Roteamento

Port Group

IP Trunk

Primary and Secondary SIP Account

32 Inbound/Outbound Routing

Manipulação de Numeros (Strings)

Digitmap

Manutenção e Upgrade

SNMP/TR069

Auto Provisionamento

Web/Telnet

Configuração de Backup/Restore

Firmware Upgrade via WEB/TFTP

Syslog and CDR

Access Rule List

Network Capture

Outward Test(GR909)

Automatic Time Synchronization

IVR local Maintenance

Cloud-based Management

Fonte de Alimentação:100-240V,50-60Hz

Consumo:

24FXS:40W; 32FXS: 45W

Temperatura Operação -10 °C ~ 45 °C

(Storage): -20 °C ~80 °C

Humidade: 10%-90% No condensation

Dimensões & Peso

24FXS:440(L)×230(W)×44(H)mm 3.0kg

32FXS:440(L)×250(W)×44(H)mm 3.2kg.